



Declaration of
Performance
January 2025
002/012025



Product Type	Traditional Lipped Casement
Manufacturer	Bereco Group Ltd Unit 5 Aspen Court Centurion Business Park Bessemer Way Rotherham S60 1FB Tel: +44 (0) 1709 838188 Email: enquiries@bereco.co.uk
Manufacturers Reference	Side Hung, Top Hung and Fixed
Intended Use	Domestic and Commercial Locations
Authorised Representative	Not Applicable
Harmonised Product Standard	BS EN 14351-1:2006 + A2:2016
AVCP System	System 3
Notified Testing Body	Chiltern Dynamics (UKAS 1762) Report Ref Chilt/P04081 Chilt/T04010-2 Chilt/T13011/10

Essential Performance Characteristic	Performance
Thermal transmittance (BS EN ISO 10077 – 1 & 2)	Less than 1.4W/m ² K
Air permeability	Class 4 – 600 Pa
Watertightness	Class 8A – 400 Pa
Resistance to wind load	Class 5C – 2000 Pa
Dangerous substances	None
Acoustic	No less than 31Db
Load-bearing capacity of safety devices	350N (If fitted)
Impact Resistance	NPD
Radiation Properties	LT: 70% - 82% (depending on glass configuration) G: 37% - 65% (depending on glass configuration)

This Declaration of Performance supports UKCA marking as required from 1 January 2021.

This declaration is issued under the sole responsibility of the manufacturer, or his representative.

Signed on the behalf of the manufacturer

Name and Title: Nicola Harrison – Managing Director

Signature: _____

Date of Issue: 01/01/2025