



Declaration of
Performance
June 2013
003/062013



Product Type	Traditional Flush Casement
Manufacturer	Bereco Group Ltd Unit 5 Aspen Court Centurion Business Park Bessemer Way Rotherham S60 1FB Tel: +44 (0) 1709 838188 Email: enquiries@bereco.co.uk
Manufacturers Reference	Side Hung, Top Hung and Fixed
Intended Use	Domestic and Commercial Locations
Authorised Representative	Not Applicable
Harmonised Product Standard	BS EN 14351-1:2006 + A1:2010
AVCP System	System 3
Notified Testing Body	Chiltern Dynamics (UKAS 1762) Report Ref Chilt/P04081 Chilt/T04010-2 Chilt/T13011/02

Essential Performance Characteristic	Performance
Thermal transmittance (EN ISO 10077 – 1 & EN ISO 10077-2)	Less than 1.6W/m ² K
Air permeability	Class 3
Watertightness	Class 8A
Resistance to wind load	Class 5C
Dangerous substances	None
Acoustic	No less than 31Db
Load-bearing capacity of safety devices	350N (If Fitted)
Impact Resistance	NPD
Radiation Properties	LT: 80% G: 60%

This declaration is issued under the sole responsibility of the manufacturer, or his representative.

Signed on the behalf of the manufacturer

Name and Title: Kevin Martin – Managing Director

Signature:

Date of Issue: 27/06/2013